

	LIGHT PRODUCT HANDLING	MEDIUM PRODUCT HANDLING			HEAVY PRODUCT HANDLING		FIXED AND VEHICLE MOUNT COMPUTERS	
	CS40	CN50	CK3X	CK3R	CN70/CN70e	CK70 / CK71	CV60	CV61
Applications	Sales; Merchandising; Home and Office Field Service; Truckload Transportation	Field Service; Sales; Merchandising; DSD; ITV; Courier Express; Postal Vehicle; Postal Pedestrian	In-premise; Retail; Industrial; Distribution; Crossdock	In-premise; Retail; Industrial; Distribution; Crossdock	Field Service, DSD; Enterprise Asset Management; LTL; Courier Express; Postal Vehicle; Airline Baggage and Cargo	Parcel Delivery (CEP & Home Delivery); Crossdock Manufacturing; Warehousing (including 3PL)	Manufacturing and Warehousing	
Durability	1.2 m (4 ft) drops per MIL-STD 810G; IP54	1.5 m (5 ft) across all temperatures drops per MIL-STD 810G, 1000 (.5 m) tumbles; IP54	1.5 m (5 ft) across all temperature range drops per MIL-STD 810G; 1000 (.5 m) tumbles; IP54	1.2m (4 ft) across all temperatures drop per MIL-STD 810G; 1000 (.5 m) tumbles; IP54	2.4 m (8 ft) at ambient, 1.8 m (6 ft) across all temperatures drops per MIL-STD 810G, 2,000 (1 m) tumbles per IEC 60068-2-32 specification; IP67		Standard operating temp -20° to 50°C, MIL STD 810F, IP65	Standard operating temp -20° to 50°C, MIL STD 810F, IP66
Operating System	Windows Embedded Handheld 6.5	Windows Mobile 6.1 Windows Embedded Handheld 6.5	Windows Embedded Handheld 6.5		Windows Handheld Embedded 6.5		Windows CE.NET 4.2, Windows XP Professional	Microsoft Windows 7 Professional, Windows XP Professional
Display	2.8 " QVGA color touch, embedded accelerometer	3.5" QVGA color, touch, embedded accelerometer	3.5" QVGA color, touch panel with ambient light sensor, embedded accelerometer	3.5" QVGA color, touch panel with ambient light sensor	3.5" VGA color, high durability touch panel with ambient light sensor, embedded accelerometer		12.1" 800x600 SVGA	12.1" 1024x768 XGA
Memory / Storage	256 MB RAM 512 MB Flash MicroSD slot for removable memory cards up to 32GB	256 MB RAM 512 MB Flash MicroSD slot for removable memory cards up to 32GB	256 MB RAM 1 GB Flash Micro-SD slot for removable memory cards up to 32 GB	256 MB RAM 512MB Micro-SD slot for removable memory cards up to 32 GB	512 MB RAM 1 GB Flash MicroSD slot for removable memory cards up to 32GB		256 MB RAM, 512 KB Flash, expansion slot supporting 512 MB	1 GB for Windows XP, 2 GB for Windows 7, expansion slot supporting 32 GB
Scanner and Camera Options	3.2 MP fixed focus color camera and 2D imager – both standard	1MP area imager 3.1 MP color camera with autofocus and flash	High Performance 2D Area Imager, High Performance 2D Near-Far Area Imager	High Performance 2D imager	High Performance 2D Area Imager and 5 MP color camera with LED flash option	High Performance 2D Area Imager, 2D Near-Far Area Imager (CK71), Linear Imager (CK71), and 5 MP color camera with LED flash option	Tethered serial bar code scanner, Tethered RFID scanner	Tethered serial scanner, Tethered USB bar code scanner, Tethered RFID reader
Radio Type Options	802.11 b/g CCX v4 or WAPI (China) Bluetooth® 2.1 + EDR GSM/GPRS/EDGE/UMTS/HSDPA-HSUPA Integrated GPS (stand-alone or assisted)	802.11 a/b/g/n Cisco Compatible CCX Bluetooth v2.1 EDR	802.11 a/b/g/n Cisco Compatible CCX Bluetooth v2.1 EDR	802.11 b/g/n Cisco Compatible CCX Bluetooth v2.1 EDR	802.11 a/b/g/n WLAN Cisco Compatible CCX, Bluetooth 2.1 EDR; UHF RFID or WWAN: GSM/GPRS/EDGE/UMTS/HSUPA or CDMA/1xRTT/EV-DO Rev A; or Flexible Network Radio supporting UMTS/HSUPA and CDMA/EV-DO Rev A; Integrated GPS	802.11 a/b/g/n WLAN, Cisco Compatible CCX, Bluetooth 2.1 EDR	802.11 b/g, Bluetooth Compatible	802.11 a/b/g/n Cisco CCXv4 Certified
Application Development Tools	Visual Studio (2005/2008) and Eclipse							
Intermec Software	INtermec SmartSystems, INtermec Terminal Emulation, INtermec Browser, HTML5 Browser, INtermec Launcher, and INtermec Connectivity Manager, Skynax, Smart Signature Capture, eMDI (except CS40, CK3B, CV41 and CV61) and VERDEX (except CS40, CK3B, CV41 and CV61)							